



DET NORSKE VERITAS

TYPE APPROVAL CERTIFICATE

CERTIFICATE NO. S-4878
This Certificate consists of 3 pages

This is to certify that the
Cargo Securing Devices

with type designation(s)
**Tension Lever LA-9 mm;
Tension Lever LA-11 mm**


Manufactured by
ORSA LINK AB
ORSA, Sweden

is found to comply with
Det Norske Veritas' Rules for Classification of Ships

Application
Lashing equipment for securing of cargo on ships

Type	MSL, tension (kN)	MSL, shear (kN)	MSL, compr. (kN)
Tension Lever LA-9 mm	50	-	-
Tension Lever LA-11 mm	75	-	-


Place and date
Høyvik, 2007-02-06
for DET NORSKE VERITAS AS


Roald Vårheim
Head of Section



Local Office
DNV Stockholm

This Certificate is valid until
2011-06-30


Harald Olav Bjordalsbakke
Surveyor

Notice: This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

If any person suffers loss or damage which is proved to have been caused by any negligent act or omission of Det Norske Veritas, then Det Norske Veritas shall pay compensation to such person for his proved direct loss or damage. However, the compensation shall not exceed an amount equal to ten times the fee charged for the service in question, provided that the maximum compensation shall never exceed USD 2 million. In this provision "Det Norske Veritas" shall mean the Foundation Det Norske Veritas as well as all its subsidiaries, directors, officers, employees, agents and any other acting on behalf of Det Norske Veritas.



Cert. No.: S-4878

File No.: 924.10

Product description

Tension Lever, for securing of cargo.

Application/Limitation

Breaking load in tension:

- LA-9 mm = 100 kN
- LA-11 mm = 150 kN

Tests to be carried out:

- Production testing: 0,5% of the items shall be proof tested to 1.1 x MSL, with realistic test setup and load application.
- Material tests are to include impact testing at 0° C, with the impact energy requirements according to DNV Rules Pt.5 Ch.2 Sec.6 D200.

Products manufactured according to this TA shall be inspected by a DNV surveyor, and in addition the DNV surveyor shall witness the production testing and issue DNV product certificates for each batch. Alternatively based on a Manufacturing Survey Arrangement with DNV, the certificates may be issued by the manufacturer.

Materials shall be according to approved drawings or equivalent, and to be delivered with works material certificates.

Type Approval documentation

Approved drawings:
Tension Lever Type LA

Drawing No.:

Rev.:
04-06-14

Approval letter: MTPNO876/HOBY/262.1-002686-J-5, dated 2007-02-06.

Prototype test report No. SKM-06-4384-2 from DNV Stockholm, dated 2006-11-06.

Tests carried out

Prototype tested according to the Rules

Marking of product

Each item to be marked by manufacturer for traceability.





Cert. No.: S-4878
File No.: 924.10

Certificate retention survey

As required by the local DNV office, but intervals not to exceed 4 years.

END OF CERTIFICATE

